

FEATURES



A. LUMBAR SUPPORT

Static Lumbar Support Located at 5.5" to 17" above compressed seat height. Ratchet height back adjustment with 2" of travel. Intuitively designed back which provides ergonomic thoracic support in either standard seating position or reverse straddled.

B. MECHANISM

Swivel mechanism with variable or free float back angle adjustment, seat slider depth adjustment, pneumatic lift height adjustment.

C. ENERSORB™

Energy absorbing ENERSORB™ in seat and back for comfortable ergonomic support--reduces sitting fatigue by minimizing pressure points, increases blood circulation, and promotes good posture

D. BASE AND CASTERS

5 Star Polished Aluminum Base with non-marking 2" polyurethane soft wheel casters.



1864DS

Dimensions

Model 1864

Overall Width (Outer arm to outer armrest)	24"
Overall Depth (Front seat to back of back rest)	18" - 20"
Overall Height (Floor to top of back rest)	37" - 44"
Seat Width	18"
Back Width	21"
Back Height (From compressed seat)	20" - 22"
Seat Height	19" - 24"
Seat Depth	17" - 19"



Dimensions

Model 1864DS

Overall Width (Outer arm to outer armrest)	25"
Overall Depth (Front seat to back of back rest)	25" - 27"
Overall Height (Floor to top of back rest)	40½" - 48"
Seat Width	17½"
Back Width	24½"
Back Height (From compressed seat)	16½" - 19½"
Seat Height	22½" - 30"
Seat Depth	16½" - 18½"

