

Stafford Specifications

Worksurfaces

- ✓ Worksurfaces are 1 3/16" thick with Red Oak hardwood 1/4" round-overs on the edges
- ✓ Top surfaces are High Pressure Laminate (HPL) for durability and abrasion resistance, in Victorian Cherry or Noble Mahogany.

Casements

- ✓ Side panels are 3/4" high density engineered core wood composite finished on both sides with Thermo-fused laminate, offering premium quality abrasion and stain resistant surfaces.
- ✓ Side panels are banded on the bottom and all exposed edges for additional strength and to seal out moisture.

Pedestals and Drawers

- ✓ Drawer faces are 3/4" high density engineered core wood composite finished on both sides with Thermo-fused laminate, offering premium quality abrasion and stain resistant surfaces.
- ✓ Pedestal file drawers are standardized with filing support rails, accepting letter hanging files, to accommodate front-to-back or side-to-side filing options.
- ✓ Lateral file drawers are standardized with filing support rails, accepting letter or legal hanging files, to accommodate front-to-back or side-to-side filing options.
- ✓ Box drawers operate on full extension ball-bearing slides, tested for 75lbs.
- ✓ File drawers operate on full extension ball bearing slides, tested for 100lbs.
- ✓ Lateral file drawers operate on full extension ball bearing slides, tested for 150lbs.
- ✓ Lateral file drawers are 16 1/2" deep
- ✓ Box drawers and File drawers are 20 7/8" deep. (desks).
- ✓ Box drawers and File drawers are 14 7/8" deep. (returns).

Hutch attachments

- ✓ Hutches are attached with hard mounted connectors.

- ✓ Hutch back panels are recessed 2" from the worksurface for wire management purposes.

Grommets

- ✓ Grommets are 1 3/4" in diameter and are black.